

NITRO Spreaders

TUBE•LINE™

NITRO

MANURE SPREADERS

LS / RS / Commercial
Series



www.tubeline.ca



Table of Contents

Features and Options

Apron Chains	4
Quick-Drop Beaters	5
Vertical Beaters	6
Spinner Deck	7
NITRO Box.	8
Axles & Tires	10
Tri-Axle	12
Scale Systems.	19
NITRO LS.	14
NITRO RS.	16
NITRO Commercial Series.	18



Consistent Metering. Consistent Spread.

Developed with features to ensure commercial readiness, NITRO commercial series spreaders offer slip slide poly board floors and walls, a guillotine endgate, reversible apron chain, and quick drop beaters.

The guillotine endgate can be held in any position controlling how much material is able to be moved to the beaters by the variable speed apron chain. This method of delivery provides consistent metering whether working with pen pack or semi-solids. With the recent addition of the tri-axle models, you get all these features plus reduced compaction, easier turning and more.

Responding to market demand, the NITRO Low Profile(LS) and Rancher Series(RS) were developed to ensure smaller operations get the same metering in a format tailored to them. NITRO LS and RS spreaders are ideal for farmers trying to keep their yards clean while delivering rich nutrients to the field. Removeable beater assemblies provide increased value and functionality, allowing the NITRO to operate as a rear discharge trailer with a live floor when not spreading.

Under the **Apron Chain Limited Lifetime Warranty**, Tubeline will replace a broken apron chain or connecting link on any NITRO model manure spreader. Apron Chain Limited Lifetime Warranties are non-transferable.

For more information contact Tubeline Manufacturing.



Actual size.



APRON CHAINS



Hydraulic-Driven Apron Chain

The variable speed apron chain ensures that your load is delivered to the beaters at the right speed regardless of the manure consistency. This provides accurate control when metering, application speed, and thickness.

The NITRO is equipped with a fully reversible apron drive. This allows the load to be backed away from the beater assembly should foreign objects such as rocks get inbetween the beaters and jam them.



Apron Chain

The brute strength of the NITRO's apron chain system sets it apart. Truly heavy-duty, the chain and sprocket are designed to move heavy manure day after day without chain breaks.



Galvanized Slats

Apron slats are attached to the chain using a heavy tab and slot design. This free floating design minimizes stress on the joints.



Grade 80 - 3/4
Breaking Strength
113,200 lbs.

950

950TRI

1050



Grade 80 - 5/8
Breaking Strength
72,400 lbs.

300LS 275RS 450

340LS 375RS 600

440LS 575RS 750

725RS



QUICK-DROP BEATERS

Functional Versatility

All NITRO spreaders are designed to provide incredible versatility throughout the year. The NITRO is not only a capable spreader, but can be easily converted to a self unloading trailer when the beater assembly is removed.

Tubeline's Quick-Drop Beater System provides producers and custom operators an adaptive tool ideal for the transportation and processing of bulk materials.

Designed with an integrated guillotine endgate, the NITRO retains its box even with the beaters removed leaving behind a fully functional self unloading trailer with a hydraulic endgate and live floor.

The NITRO can be used to stockpile in the field throughout the year. This keeps your barnyard clean and places valuable nutrients close at hand when its time to spread.

When harvest time comes, the NITRO can be used to haul forage from the field to the pit. Open the endgate in front of the pit and run the apron to unload quickly.

Beater Removal

Remove a beater assembly in 4 steps.

1. Remove the rear most PTO drive shaft from the spreader.
2. Connect chains from a front end loader to the lift points on the beater assembly.
3. Remove the retaining bolts connecting the beaters to the box.
4. Using the loader lift the assembly from the rear of the spreader.

Note: Always remember to store your beater assemblies safely to prevent harm and/or damage. If scale system is equipped, spinner sensor must be unplugged.

VERTICAL BEATERS



Replaceable Reversible Knives

Every NITRO model is equipped with durable AR400 knives. Each knife can be easily flipped for longer life or replaced when required.



Robust and Dynamically Balanced

The NITRO beaters are dynamically balanced ensuring minimal flex and vibration when running the beaters at full speed.



Beater Wedge

275RS, 375RS, 575RS, 450, and 600 Models

A standard feature on 275RS, 375RS, 575RS, 450, and 600 models (not required on other models), the beater wedge helps to ensure manure is delivered to the beaters preventing large clumps from falling off the back of the unit.



Flange Paddle Kit

Optional

The optional bolt on paddle kit cups material to provide additional throw.

Driveline Protection

To protect expensive drive line components, NITRO spreaders are equipped with both an over running clutch and a torque limiter (Commercial and RS Series) or Shearbolt (LS Series). The over running clutch allows the beaters to freewheel after the tractors PTO drive is shut down. This prevents hard stops reducing the wear on both the NITRO and your tractor.

To prevent damage to beater assemblies, the driveline protection connects the rear PTO shaft and the beater assembly. The driveline protection disengages the driveline from the beaters should the pressure build.





Spinner Deck Beater Assembly Option


NITRO spreaders can be equipped with an optional Spinner Deck beater assembly. The interchangeable quick-drop beater system allows operators to conveniently switch between the vertical or spinner deck assemblies offering flexibility to both producers and custom operators.

Designed to maximize distribution while metering the flow of material, the Spinner Deck beater assembly utilizes a complete gear box drive system that drives both the horizontal beaters and spinners together to ensure consistent unloading.



Dual Horizontal Beaters

The NITRO Spinner Deck beater assembly comes equipped with two horizontal beaters to ensure a consistent amount of material is fed to the spinners.



Drop-On Adjustment & Dual Spinners

The lower section of the rear shield can be angled to increase material distribution over the high speed spinners.



Side Shield Kit *Optional*

The hydraulic side shield can be lowered to restrict material when spreading along the fields edge.



Available for the left or right side.

A BIG BOX FULL OF SURPRISES



Guillotine Endgate

The guillotine endgate can be opened partially to meter the amount of material being delivered to the beater assembly. This ensures the optimal delivery of lime and various manure consistencies to the field.



LED Lights

Optional

LED lights and flashers ensure transit safety. Automatic activated covers open and close in sequence with the end gate, ensuring lights are protected while spreading.



Slip Slide Poly Boards

Poly Board Walls available only on 450, 600, 750, 950, 950TRI & 1050

To resist corrosion, the NITRO box integrates slip slide poly boards on the floors of LS and RS models, and the Floors and walls of commercial models. All poly boards are secured with stainless steel hardware.



Central Grease Banks

Standard on 450, 600, 750, 950, 950TRI & 1050

Centrally located grease banks ensure easy lubrication of components located in hard to reach areas.



Industrial Jack

The strong, industrial jack, is easy to use and makes unhitching safer.



CV Shaft

Standard on Commercial and RS models

Select NITRO models come equipped with a CV (Constant Velocity) Shaft allowing for a tighter turning radius.



Suspension Tongue

*Optional on 450, 600, 725 & 750 Models
Standard on 950, 950TRI & 1050 Models*

The suspension tongue provides operator comfort and reduces mechanical stress and fatigue of both the spreader and the tractor.



Optional Colours

Optional

In addition to the standard yellow, the NITRO lineup is available in red, green, black, blue and orange.



Silage Extensions

Optional on 725, 750, 950, 950TRI & 1050

The NITRO 750 and 950 can easily double as a silage hauler, with the addition of optional height-extendors.

Note: Not for use with manure.



Rubber Seal Kit

Optional

The Rubber Seal Kit adds a compression seal to the front panel and the endgate to help contain semi solid materials.



Articulated Ball Hitch

Optional

Optional on all models is the articulated ball hitch available in various pin sizes.



Endgate Opening Gauge

Optional

With the endgate opening gauge you can quickly and easily see how open your end gate is in inches.



SINGLE AXLE

See model specifications for tire availability



19L/16.1
Implement

425/22.5
Recap Truck

550/45
R22.5

480/70
R30

600/65
R34

710/70
R38

710/70
R42



Consistent Loading Height

Single & tandem axles

Each axle is specifically engineered to match the selected tire size. This attention to detail ensures that each spreader that leaves our plant can be easily loaded.



Brakes

Optional for single & tandem

The optional brake system comes with a total of 4 calipers. Single axle spreaders are configured with one large caliper per rotor. Tandem axle spreaders are configured with one caliper per rotor.

Single axle shown. Braking configurations may vary with model. All models are brake ready.

Note: For model applications please see pages 14-18.



TANDEM AXLE

See model specifications for tire availability



11R-22.5
Truck Tire

16.5L/16.1
Implement

425 x 22.5
Recap Truck

550/45
R22.5

700/50
R26.5

750/60
R30.5

**Also used for Tri-axle spreaders*



Adjustable Axle Position

Commercial Series

Our Commercial Series spreaders have 3 axle positions which help to optimize the spreaders balance while traveling through the field.



High Load Bearings

Standard on Tandem Axles

The walking beam tandem axle pivot bearings on the Commercial Series spreaders use high load composite bearings with embedded lubricant. This eliminates the need to grease them during maintenance.

Note: Tire scaling is approximate. Tire profiles and rims may not be exactly as shown, images are intended for reference only.



TRI-AXLE THE MORE THE MERRIER



**Less
Compaction**



**Extended
Life**



**Easy
Turning**




**Heavier
Duty**

NITRO Tri-Axle spreaders feature the standard NITRO Quick-Drop Beater assembly, allowing you to switch quickly and easily between the vertical beaters and the spinner deck. While the vertical beater assembly is ideal for thicker material, the spinner deck is ideal for looser material such as poultry litter. This set-up offers increased flexibility for both producers and custom operators allowing you to equip your spreader properly for whichever material you'll be spreading.

It has 16,000lbs (10 bolt) wheel hub capacity. Due to the increased amount of contact points, the Tri-Axle results in reduced soil compaction. This allows for more air and water to get to the roots, increasing the yield of your crops when compared to single and tandem axles.


They also come standard with a following axle. The front and rear axles can turn independently, reducing wear on the tires when turning giving your tires longer life.

Brakes are available on Tri-Axle models on both the centre and rear axles. Each axle also comes standard with the Horst Road Flex Suspension system, reducing wear on the NITRO box when driving down the road or in the field.



Load Transfer Draw Bar


Hydraulically transfer the load by dispersing the weight to the tongue when unit is full to increase traction and help you stop quicker.



Follow Axles

Follow axles allow for a sharper turning radius.

For predictable towing or reversing, following axles can be hydraulically locked in line.



15° Rotation

Front and rear axles allow a swivel of 15° in each direction giving the Tri-Axle design a great turning radius.

Wheel independent Road Flex suspension. This patented innovation not only smooths out bumps, it gives added clearance when turning adding even more protection for your load.



NITRO^{LS} Low Profile Series



BEATER TYPE



AXLE CONFIGURATIONS



NITRO^{RS} Rancher Series



BEATER TYPES



SPINNER
DECK

AXLE CONFIGURATIONS



NITRO Commercial Series



BEATER TYPES



SPINNER
DECK

AXLE CONFIGURATIONS



↑↓ **60"** **MINIMUM
LOADING
HEIGHT**

540 **RPM** 
BEATER SPEED

6-10 **TON
CAPACITY**

Standard Features

- Guillotine end gate
- Front stone guard
- Steel sidewall
- Poly board floor
- Removable/replaceable apron slats
- Hydraulic drive on apron chain to accurately adjust feed speed
- Quick removable beaters for windrowing, etc.
- Robust heavy duty logging style apron chain with a **LIMITED LIFETIME WARRANTY**

↑↓ **69"** **MINIMUM
LOADING
HEIGHT**

**UP
TO** **420** **RPM** 
BEATER SPEED

10-19 **TON
CAPACITY**

Standard Features

- Guillotine end gate
- Front stone guard
- Steel sidewall
- Poly board floor
- Removable/replaceable apron slats
- Hydraulic drive on apron chain to accurately adjust feed speed
- Quick removable beaters for windrowing, etc.
- Spinner deck option available
- Robust heavy duty logging style apron chain with a **LIMITED LIFETIME WARRANTY**

↑↓ **77"** **MINIMUM
LOADING
HEIGHT**

**UP
TO** **420** **RPM** 
BEATER SPEED

13-30 **TON
CAPACITY**

Standard Features

- Guillotine end gate
- Front stone guard
- Steel sidewall
- Poly board floor
- Hydraulic drive on apron chain to accurately adjust feed speed
- Removable/replaceable apron slats
- Spinner deck option available
- Poly board sidewall
- Quick removable beaters for windrowing, etc.
- Side mounted access ladder
- Suspension tongue (Standard on 950, 950TRI & 1050 Models only)
- Robust heavy duty logging style apron chain with a **LIMITED LIFETIME WARRANTY**

LOW PROFILE DESIGN

Productivity Within Reach

The low profile design allows the LS series to be fully loaded with skid steers and small loaders.



LS Series



Specifications	NITRO 300LS
Carrying Capacity	6 Ton
Heaped (cu. ft.)	300
Struck Level (cu. ft.)	171
Inside Dimensions	62"W x 27"D x 159.8"L (Inside width between flare 80.75")
Overall Length	23.5'
Overall Outside Width (Single Axle)	110"
Overall Outside Width (Tandem Axle)	N/A
Loading Height (Single Axle)	60"
Loading Height (Tandem Axle)	N/A
Specifications	NITRO 300LS
Wheel Hub Capacity (Tandem Axle)	N/A
Tandem Tire Sizes	N/A
Wheel Hub Capacity (Single Axle)	12,000lbs (10-bolt) x2
Single Tire Sizes	19L-16.1 Implement 550/45-22.5 Flotation /Bias Ply 11R-22.5 New/Used Truck Tire 425/22.5 Truck Tire
Beater Diameter	32"
Beater Speed	540 RPM
PTO Speed	540 RPM
Apron Chain Link Dia.	5/8"
Shipping Weight	6,250 lbs. / 2,835 kg
Required Tractor PTO HP	50
Brakes Available	No

Note: Specifications are subject to change without notice.
Capacities determined by ASAE Std S324.2



Specifications	NITRO 340LS	NITRO 440LS
Carrying Capacity	8 Ton	10 Ton
Heaped (cu. ft.)	344	440
Struck Level (cu. ft.)	187	256
Inside Dimensions	62"W x 27"D x 174.38"L (Inside width between flare 80.75")	62"W x 31"D x 206.44"L (Inside width between flare 80.75")
Overall Length	24.5'	27.5'
Overall Outside Width (Single Axle)	N/A	N/A
Overall Outside Width (Tandem Axle)	107"	107"
Loading Height (Single Axle)	N/A	N/A
Loading Height (Tandem Axle)	62.75"	67"

Specifications	NITRO 340LS	NITRO 440LS
Wheel Hub Capacity (Tandem Axle)	8,000 lbs. (8-bolt) x4	8,000 lbs. (8-bolt) x4
Tandem Tire Sizes	16.5-16.1 Implement 550/45-22.5 Flotation /Bias Ply 11R-22.5 New/Used Truck Tire 425/22.5 Truck Tire	16.5-16.1 Implement 550/45-22.5 Flotation /Bias Ply 11R-22.5 New/Used Truck Tire 425/22.5 Truck Tire
Wheel Hub Capacity (Single Axle)	N/A	N/A
Single Tire Sizes	N/A	N/A

Beater Diameter	32"	32"
Beater Speed	540 RPM	540 RPM
PTO Speed	540 RPM	540 RPM
Apron Chain Link Dia.	5/8"	5/8"
Shipping Weight	7,128 lbs. / 3,240 kg	8,050 lbs. / 3651.4 kg
Required Tractor PTO HP	60	100
Brakes Available	No	No



Under the **Apron Chain Limited Lifetime Warranty**, Tubeline will replace a broken apron chain or connecting link on any NITRO model manure spreader. Apron Chain Limited Lifetime Warranties are non-transferable.

For more information contact Tubeline Manufacturing.

RS Series



NITRO 275RS



NITRO 375RS

Specifications	NITRO 275RS	NITRO 375RS
Carrying Capacity	10 Ton	13 Ton
Heaped (cu. ft.)	294	444
Struck Level (cu. ft.)	201	266
Inside Dimensions	62.5"W x 34.5"D x 143"L (Inside width between flare 77.75")	62.5"W x 34.5"D x 175"L (Inside width between flare 89")
Overall Length	23.5'	25'
Overall Outside Width (Single Axle)	118"	126"
Overall Outside Width (Tandem Axle)	115.5"	115"
Loading Height (Single Axle)	69"	76"
Loading Height (Tandem Axle)	69"	75"

Specifications	NITRO 275RS	NITRO 375RS
Wheel Hub Capacity (Tandem Axle)	12,000 lbs. (8-bolt) x4	12,000 lbs. (8-bolt) x4
Tandem Tire Sizes	425/22.5 Recap Truck Tires 550/45-22.5 Flotation Tires	425/22.5 Recap Truck Tires 550/45-22.5 Flotation Tires
Wheel Hub Capacity (Single Axle)	16,000lbs (10-bolt) x2	16,000lbs (10 bolt) x2
Single Tire Sizes	425/22.5 Recap Truck Tires 550/45-22.5 Flotation Tires 480/70-30 Tractor Lug Tire	600/65-34
Beater Diameter	34"	34"
Beater Speed	420 RPM	420 RPM
PTO Speed	1000 RPM	1000 RPM
Apron Chain Link Dia.	5/8"	5/8"
Shipping Weight	8,800 lbs. / 3,992 kg	9,139 lbs. / 4,145 kg
Required Tractor PTO HP	80	90
Brakes Available	Yes	Yes



Under the **Apron Chain Limited Lifetime Warranty**, Tubeline will replace a broken apron chain or connecting link on any NITRO model manure spreader. Apron Chain Limited Lifetime Warranties are non-transferable.

For more information contact Tubeline Manufacturing.



NITRO 575RS



NITRO 725RS

Specifications	NITRO 575RS	NITRO 725RS
Carrying Capacity	16 Ton	19 Ton
Heaped (cu. ft.)	576	767
Struck Level (cu. ft.)	379	507
Inside Dimensions	62.5"W x 45.5"D x 218"L (Inside width between flare 94")	71"W x 50"D x 240"L (Inside width between flare 96")
Overall Length	27.5'	31'
Overall Outside Width (Single Axle)	131"	136"
Overall Outside Width (Tandem Axle)	116"	136"
Loading Height (Single Axle)	88.5"	93"
Loading Height (Tandem Axle)	80"	93"

Specifications	NITRO 575RS	NITRO 725RS
Wheel Hub Capacity (Tandem Axle)	12,000 lbs. (8-bolt) x4	16,000 lbs. (10-bolt) x4
Tandem Tire Sizes	425/22.5 Recap Truck Tires 550/45-22.5 Flotation Tires 700/50-26.5 Flotation Tires	700/50-26.5 Flotation Tires
Wheel Hub Capacity (Single Axle)	12,000lbs (8-bolt) x4	20,000 (10 bolt) x2
Single Tire Sizes	710/70 R38 Tractor Lug Tire	710/70 R42 Tractor Tires
Beater Diameter	34"	36"
Beater Speed	420 RPM	405 RPM
PTO Speed	1000 RPM	1000 RPM
Apron Chain Link Dia.	5/8"	5/8"
Shipping Weight	11,000 lbs. / 4,990 kg	15,652 lbs. / 7,099 kg
Required Tractor PTO HP	125	165+
Brakes Available	Yes	Yes

Note: Specifications are subject to change without notice. Capacities determined by ASAE Std S324.2

Commercial Series



NITRO 450

NITRO 600

Specifications	NITRO 450	NITRO 600
Carrying Capacity	13 Ton	17 Ton
Heaped (cu. ft.)	481	636
Struck Level (cu. ft.)	290	406
Inside Dimensions	62"W x 40"D x 201"L (Inside width between flare 97.5")	62"W x 50"D x 227"L (Inside width between flare 97.5")
Overall Length	27'	29.5'
Overall Outside Width (Single Axle)	115"	131"
Overall Outside Width (Tandem Axle)	116"	131"
Loading Height (Single Axle)	77"	90"
Loading Height (Tandem Axle)	79" (550/45-22.5) 77" (425/22.5 recap truck)	85" (550/45-22.5) 92" (700/50-26.5) 87" (425/22.5 recap truck)

Specifications	NITRO 450	NITRO 600
Wheel Hub Capacity (Tandem Axle)	12,000 lbs. (8 bolt) x4	16,000 lbs. (10 bolt) x4
Tandem Tire Sizes	550/45-22.5 or 425/22.5 recap truck	550/45-22.5, 700/50-26.5 425/22.5 recap truck
Wheel Hub Capacity (Single Axle)	16,000lbs (10 bolt) x2	20,000lbs (10 bolt) x2
Single Tire Sizes	600/65-34	710/70-38
Beater Diameter	34"	34"
Beater Speed	420 RPM	405 RPM
PTO Speed	1000 RPM	1000 RPM
Apron Chain Link Diameter	5/8"	5/8"
Shipping Weight	11,355 lbs. / 5,151 kg	13,930 lbs. / 6,319 kg
Required Tractor PTO HP	125+	150+
Brakes Available	Yes	Yes



Under the **Apron Chain Limited Lifetime Warranty**, Tubeline will replace a broken apron chain or connecting link on any NITRO model manure spreader. Apron Chain Limited Lifetime Warranties are non-transferable.

For more information contact Tubeline Manufacturing.



NITRO 750



NITRO 950

Specifications	NITRO 750	NITRO 950
Carrying Capacity	20 Ton	25 Ton
Heaped (cu. ft.) (with Optional Silage Extension)	838 1,038	1,028 1,252
Struck Level (cu. ft.) (with Optional Silage Extension)	560 770	695 918
Inside Dimensions	67"W x 58"D x 252"L (Inside width between flare 102.5")	67"W x 58"D x 297"L (Inside width between flare 102.5")
Overall Length	32.5'	35.25'
Overall Outside Width (Single Axle)	140"	N/A
Overall Outside Width (Tandem Axle)	140"	140"
Loading Height (Single Axle) (with Optional Silage Extension)	100" 116"	N/A N/A
Loading Height (Tandem Axle) (with Optional Silage Extension)	102" 118"	109" 125"

Specifications	NITRO 750	NITRO 950
Wheel Hub Capacity (Tandem Axle)	16,000 lbs. (10 bolt) x4	20,000 lbs. (10 bolt) x4
Tandem Tire Sizes	700/50-26.5	750/60-30.5 Flotation Tires 750/60-30.5 Flotation Tires (Radial)
Wheel Hub Capacity (Single Axle)	20,000lbs (10 bolt) x2	N/A
Single Tire Sizes	710/70-42	N/A
Beater Diameter	36"	36"
Beater Speed	405 RPM	405 RPM
PTO Speed	1000 RPM	1000 RPM
Apron Chain Link Diameter	5/8"	3/4"
Shipping Weight	16,195 lbs. / 7,346 kg	19,890 lbs. / 9,022 kg
Required Tractor PTO HP	180+	200+
Brakes Available	Yes	Yes

Note: Specifications are subject to change without notice. Capacities determined by ASAE Std S324.2



NITRO 950TRI

NITRO 1050

Specifications	NITRO 950TRI	NITRO 1050
Carrying Capacity	25 Ton	30 Ton
Heaped (cu. ft.) (with Optional Silage Extension)	1,028 1,252	1,159 1,509
Struck Level (cu. ft.) (with Optional Silage Extension)	695 918	769 1,159
Inside Dimensions	67"W x 58"D x 297"L (Inside width between flare 102.5")	67"W x 58"D x 324"L (Inside width between flare 102.5")
Overall Length	35.25'	39.25'
Overall Outside Width (Tri-Axle)	155"	155"
Loading Height (Tri-Axle) (with Optional Silage Extension)	108" 124"	108" 124"

Specifications	NITRO 950TRI	NITRO 1050
Wheel Hub Capacity (Tri-Axle)	16,000 lbs. (10 bolt) x6	16,000 lbs. (10 bolt) x6
Tri-Axle Tire Size	700/50-26.5 Flotation Tires 710/50-26.5 Radial Tires <i>(optional)</i>	700/50-26.5 Flotation Tires 710/50-26.5 Radial Tires <i>(optional)</i>
Beater Diameter	36"	36"
Beater Speed	405 RPM	405 RPM
PTO Speed	1000 RPM	1000 RPM
Apron Chain Link Diameter	3/4"	3/4"
Shipping Weight	22,340 lbs. / 10,133 kg	25,755 lbs. / 11,682 kg
Required Tractor PTO HP	200+	200+
Brakes Available	Yes	Yes



Under the **Apron Chain Limited Lifetime Warranty**, Tubeline will replace a broken apron chain or connecting link on any NITRO model manure spreader. Apron Chain Limited Lifetime Warranties are non-transferable.

For more information contact Tubeline Manufacturing.

Note: Specifications are subject to change without notice. Capacities determined by ASAE Std S324.2

WEIGHING IN ON OUR SPREADERS

Actual screen display from
Athene System shown.

Athene System *Variable Rate Manure Spreader Control System*

ISOBUS UT displays spreader controls and variable rate & overlap (if available on terminal)

Athene/SL2 controls spreader and scale system

- Proportional to forward speed control - ensures application rate is correct irrespective of changes in the forward speed
- Variable rate capability - allows manual or automatic adjustment of application rates in different field areas to suit conditions
- ISOBUS TC GEO compliant - allows automatic adjustment of application rates in different field areas according to a pre-defined treatment map
- ISOBUS TC sectional control compliant - simplifies operation by turning spreader on/off automatically to avoid overlaps and misses



GT 400

- Backlit LCD single line display
- External record storage option
- External printer option
- Short field names with basic entry
- Displays weight with Start-Stop Loading, Field and Zero functions



NT 560 (with AutoLog™)

- AutoLog™
- Indicator displays actual tons/acres
- View and react to tons/acre reading by speeding up or slowing down
- View/Edit 26 character field names
- View/Edit the 6 character ID
- Software to create custom reports
- Calculating the nutrient value of your manure is easy with scales on your spreader.



NITRO



TUBE•LINE™

Tubeline Manufacturing Ltd.

6455 Reid Woods Drive
Elmira, Ont. Canada N3B 2Z3
P. 1.888.856.6613 • F. 519.669.5808
sales@tubeline.ca • www.tubeline.ca